

## **Product Information**

Mod.R&S 06 | Rev.4 | Update 08/2019 | Page 1



# SUBLITHIN™ MATT LT

**Description** PU heat seal material with polyester backing, created for inkjet digital printing & cutting systems with solvent, eco-solvent or HP Latex based inks. Specifically conceived for transfers on polyester textiles colored with dye sublimation, prevents color migration, stopping sublimation effects.

Suitable for polyammide or polyester fabrics not treated.

- **Usage** Print and cut the material
  - Weed the exceeding material
  - Remove the print from the polyester backing using Siser's TTD (adhesive, transparent and resistant to high temperatures)
  - Heat apply at the conditions shown on the right
  - Remove the application tape warm (in case of other application tapes, follow specific instructions) Do not stack or fold the clothings warm in order to avoid staining of the external surface

### **Transfer settings**

Pressure: 100 gf Speed: 20 cm/sec

Average thickness

Suggested cut settings

110 microns

Blade: 45°

15 seconds at 135°C (275°F) medium pressure (3-4 bar)

Washing temperature

**Washing** Wait at least **24 hours** from application before washing. Washing resistance up to 40°C, best inside-out. Do not use bleach or other aggressive chemical agents. Not suitable for dry cleaning. Not suitable for tumble dryer.

> The product is REACH compliant The product is certified Öko-Tex® Standard 100 Class I



Dry cleaning



Tumble dryer





N.B. All information here contained are based on our experience.

We recommend to perform a test before starting standard production.

For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C



Management System ISO 9001:2015 ISO 14001:2015



The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance).

This document can be subject to variations. Updated versions are available on our website www.siser.com

For further information, please contact our Sales Office.

