# SD MAGNETMATERJAL 0,35 mm




# **SD MAGNETMATERJAL 1,27 X 30m 0,35mm** (SDMF03530127)

#### **FEATURES AND ADVANTAGES:**

- Matte white PVC bonded to magnet sheeting, is compatible for UV curable printing.
- Magnet sheeting is attracted to iron, easy to apply, remove and change, without leaving any residue.
- Without demagnetized, anti-rust

# **CONSTRUCTION DRAWING:**





#### **CUSTOMIZED SIZE:**

30M×1200/1270×0.35mm total thickness

#### Size can be customized as require

#### PACKAGING:





## PRINTING INDEX:

- O compatible
- $\Delta \quad \text{ testing required} \quad$
- × not compatible

(ECO) SOLVENT	UV CURABLE	LATEX	DYE/PIGMENT	OFFSET/FLEXO	SCREEN PRINT	TONER BASED
Δ	0	×	×	Δ	0	×

## **MAGNETIC DATA:**

Pull Strength: [9, 13] g/cm2 Guass: [110, 150] Gs

#### **PHYSICAL DATA:**

Total thickness  $0.35 \text{mm} (\pm 0.04)$ Weight  $980 \text{g/M2} (\pm 100)$ 

Opacity 100% Water resistance High

# **PROCESS AND STORAGE:**

- Working condition: temperature 15°C to 30°C, and relative humidity 30% to 60%.
- Application condition: temperature change is within 40°C daily.
- Storage condition: closed preserve avoiding sunlight, in temperature 10°C to 35°C, relative humidity 20% to 70%
- Shelf life: 12 months under storage condition. Unfinished material should be seal-packed, and used up within one month.

