

DISTINCTIVE AND UNIQUE

FOR YOUR SOPHISTICATED ADVERTISING.



SMART-X[®] DISTINCTIVE AND UNIQUE FOR YOUR SOPHISTICATED ADVERTISING

PRODUCT

SMART-X[®] the distinctive and unique lightweight foam board for sophisticated applications in the field of visual communication.

SMART-X[®] is a lightweight, all-plastic sheet material with surfaces of UV and weather resistant solid polystyrene (HIPS) and a core of expanded polystyrene that is completely moisture-resistant. These characteristics make SMART-X[®] the world's only lightweight foam board for external applications without any significant change in colour for a period of up to two years. Due to its refined surface structure and the large format production (up to 2 metres width) SMART-X[®] is also perfectly suited for direct digital printing.

Moreover, SMART-X[®] is a mono-material composite made from 100% polystyrene and, therefore, perfectly meets the demand for ecological materials in the area of visual communication.

SMART-X[®] – AT A GLANCE

- High stability and very low weight
- Very good resistance to weathering with high UV stability and humidity resistance, no deformation
- Refined surface structure
- Brilliant printing results with direct digital printing
- Also available in 2 metres width
- Temperature resistance from -10°C up to +70°C
- Low resistance during contour milling

SMART-X[®] – THE GREEN ASPECT

- SMART-X[®] is a mono-material composite made from 100 % polystyrene (no adhesive between core and cover layers)
- Ecological SMART-X[®] with a homogeneous compound is 100% recyclable
- About 95% of the production waste of the SMART-X[®] production is collected and recycled on-site

APPLICATION

PRINTING - CUTTING - ASSEMBLING

SMART-X[®] can be used with all lamination and printing techniques for applications in the field of advertising signage, event marketing and POS/POP displays. Thanks to the excellent ratio of extremely low weight and high rigidity and flatness, SMART-X[®] is ideal for the following two-dimensional applications:

All types of signage, especially large-format or long and narrow signs – formats where other materials usually deform.

 Optimal for self-supporting, free-standing structures
directly printed – milled – shipped flat – assembled on site.

Life-sized fashion displays made from SMART-X[®] – directly printed – contour milled – assembled on site – ready to go!

Our customers are convinced of the unique qualities of SMART-X[®]. Major furniture stores, DIY stores, food retail chains as well as suppliers of POS/POP displays and service providers in the event marketing industry are just a few examples of the satisfied SMART-X[®] customer base.

Additional safety requirements and detailed processing instructions for SMART-X[®] can be received upon request.



SMART-X[®]

PRODUCT RANGE

Colour	☐ white			
Thickness	5 mm / 10 mm	19 mm		
Standard formats (WxL)		1220 x 2440 mm 1220 x 3050 mm 2030 x 3050 mm		
Protective film	on one side	both sides		



PRODUCT INFORMATION

Thickness		5 mm	10 mm	19 mm
Weight		1 kg/m ²	1,90 kg/m ²	3 kg/m ²
Flexural strength	EN ISO 178	10 MPa	7 MPa	5 MPa
E-modul (bending test)	EN ISO 178	600 MPa	400 MPa	200 MPa
Service temperature	_		up to 70°C	
Thermal expansion	DIN EN ISO 75-2		0,08 mm/(mK)	

🛟 100% homogeneous polystyrene – recyclable

ROHS DIRECTIVE

SMART-X[®] meets the requirements of the RoHS/WEEE directives of the European Union on the restriction of hazardous substances. SMART-X® foam boards do not contain lead, mercury, cadmium, hexavalent chromium, phthalate, formaldehyde, CFCs, asbestos, plasticizer nor silicone.

REACH REGULATION

SMART-X® meets the requirements of the current version of the European Union chemicals regulation (REACH). In particular, SMART-X® foam boards do not contain any of the substances which are listed in the current version of the ECHA Candidate List of "Substances of Very High Concern" (SVHC).

PROCESSING AT A GLANCE

Laminating/

Mounting



Digital printing





Overlac-

quering/

Varnishing



Sawing



Contour

cutting/

Contour

milling



Laser cutting



folding



Gluing

Routing and (V-groove cut)





3A Composites GmbH Alusingenplatz 1 78224 Singen Germany

+49(0)7731-941 29 89 Tel. +49(0)7731-941 21 05 Fax EMail display.eu@3AComposites.com www.smart-x.eu