

ImagePerfect™ 2830-201 is an embossed laminate with a permanent, solvent-based adhesive system that has been specifically designed for protecting indoor floorminder graphics. It also delivers an R10-rated non-slip surface.

IP 2830-201

ImagePerfect™ 2830-201 is a textured laminate that provides a non-slip (R10), scuff-resistant surface finish with high resistance to wearing. In application, it has a high level of transparency. It should be used as a match-component laminate in conjunction with IP 2521 as the harmonised print media for indoor floor graphic installations. In order to avoid potential lifting of the product, we would recommend that corners are rounded rather than cut to a sharp 90° angle. This laminate must be applied dry (not compatible with wet application).

Specifications	
DESCRIPTION	Indoor floor minder vinyl laminate
COLOUR	Clear matt
THICKNESS	200μ
WEIGHT	N/A
ADHESIVE	Solvent based acrylic, permanent
ADHESIVE STRENGTH	11N / 25mm (Finat TM 1/24h)
ANTI SLIP RATING	R10 (DIN 51130)
RELEASE PAPER	N/A
TEMPERATURE RANGE	-30°C to +90°C
DURABILITY (UNPRINTED)	6 months
FLAME RETARDANCY	B1
SHELF LIFE	2 years, 20°C / 50% humidity
RECOMMENDATION	For optimum quality, please ensure that the media feed adjustment has been completed for this material

© March 2020 Spandex Group. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners.

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information. They are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for its specific use, not least with regard to possible application-related influences. All technical data are subject to change.

The durability expectation is based on mid European exposure conditions. The actual performance life will depend on substrate preparation, exposure conditions and the maintenance of the applied product. For instance, exterior performance will typically decrease in the case of installations facing south, in areas of extended exposure to high temperatures (such as southern European countries), in industrially polluted areas or in areas of high altitude. Also, for horizontal applications, exterior performance will typically be impacted.

In the event of improper use and/or incorrect processing that does not comply with our instructions, any liability is excluded, including that for follow-up costs.

Digital: The print media should be completely dry before further processing, such as cutting, laminating, varnishing or application, or the residual solvents could otherwise change the specific features of the product. To ensure the best possible outcome, the match-component ImagePerfect™ profile should be used with the relevant ImagePerfect™ print media.