

Overview:

DF/DFL1 | Digiflör® Tactile fire-rated cushioned vinyl flooring 1000gsm

Introducing Digiflör Tactile - our cushioned flooring that has been devised especially for outstanding printed floor designs. Digiflör Tactile not only gives superb print results but also offers a high level of durability. The specifically-developed cushioned backer lends acoustic properties that can help to absorb excess noise, transforming interior spaces into more welcoming customer-friendly zones. We've also ensured that this product is fully fire-rated, making it the perfect choice for exhibitions, events and any place that requires a safe, sumptuous and perfectly-printable flooring.

- EN 13501 fire rating for added safety
- Fully printable bring your clients' ideas to life!
- Ink receptive top coating to aid durability
- Woven middle layer for increased tensile strength
- Cushioned backing helps to absorb excess noise
- Ideal for indoor spaces with low-to-medium traffic

Applications:

Our foot-friendly cushioned flooring adds another level of quality to interior spaces; utilising a fully printable surface and acoustic properties to provide a truly premium flooring experience. Perfect for exhibitions, POS, retail spaces and much more.

Compatibility:

This product has been tested for use with the following ink technologies;

Latex

UV-Curable

Suitable for use on printers that can accommodate at least 2.2mm product thickness.

For roll fed machines; please check that the machine can take the weight of the roll. (1600mm x 20m = 33kgs, 2200mm x 20m = 45kgs and the 3160mm x 20m = 65kgs). Please note, for Latex printing this product is only compatible with HP Latex 1500, 3000, 3100, 3200, 35000, R1000, and R2000 printers.

Usage and durability:

Digiflor can be laid on any hard, smooth surface such as hardboard, wood, concrete or stage decking and can be cleaned by using a diluted non-chlorine detergent

Suitable for use on printers that can accommodate at least 2.2mm product thickness. For roll fed machines; please check that the machine can take the weight of the roll.

The lifetime of this product depends on location and the amount of foot traffic, however it's typically designed to last at least six months under light to medium traffic.

Please note, for Latex printing this product is only compatible with HP Latex 1500, 3000, 3100, 3200, 35000, 3600, R1000, and R2000 printers.

Certifications:

Slip rating - BS 7976-2: 2002 Pendulum Test

Fire rating - EN 13501-1: Bfl-s1

Specifications:

Substrate weight 1000 gsm
Substrate thickness 2000 mic

Tensile Strength Warp 1500 N/5cm DIN 53354 BS 3424 Method 6A
Tensile Strength Weft 800 N/5cm DIN 53354 BS 3424 Method 6A
Tear Strength Warp 50 N DIN 53356 BS 3424 Method 7A
Tear Strength Weft 35 N DIN 53356 BS 3424 Method 7A
Thickness 2mil

Papergraphics UK:

ADDRESS	PHONE	WEBSITE
Crompton Way, Crawley, West Sussex, RH10 9QR	0845 1300 662	paper-graphics com

CAVEAT EMPTOR: WE HAVE CONDUCTED IN-HOUSE TRIALS ON ALL OF OUR PRODUCTS TO MAKE SURE THEY MAKE THE GRADE IN PERFORMANCE AND SUITABILITY. BUT THERE ARE SCORES OF VARIABLES IN THE COMBINATIONS OF SOFTWARE, HARDWARE, PRINT PROFILES, SPEEDS & RESOLUTIONS, SO WE REALLY DO RECOMMEND THAT YOU UNDERTAKE YOUR OWN EVALUATION WITH YOUR OWN EQUIPMENT TO MAKE SURE THAT OUR PRODUCTS MEET YOUR EXPECTATIONS.



Overview:

DF/DFL1 | Digiflör® Tactile fire-rated cushioned vinyl flooring 1000gsm

Availability:

Our products come in many shapes & sizes, however, as market requirements change, so do the range of sizes we produce and hold in stock. The following reflects the main product dimensions we supply this product in as at the time this data sheet was created. If the size you need isn't listed, please speak to us to see if it can be made especially for you.

Product Code (SKU)	Width	Length
DF/DFL1/110010/76/1	1100 mm	10 M
DF/DFL1/160020/76/1	1600 mm	20 M
DF/DFL1/220020/76/1	2200 mm	20 M
DF/DFL1/320020/76/1	3200 mm	20 M

Papergraphics UK:

ADDRESS	PHONE	WEBSITE
Crompton Way, Crawley, West Sussex, RH10 9QR	0845 1300 662	paper-graphics.com