

NESCHEN ECOLAM 1650



NEW NEW NEW NEW NEW NEW NEW NEW NEW NEW NEW NEW NEW NEW

"The new EcoLam is made for cost conscious customers who demand our original Neschen Quality."

Stephan Liegerer - Head of Technical Service

PRODUCT FEATURES

- Integrated compressor for constant pressure
- Heat assist through heatable top roller
- Large rollers with optimum pressure distribution
- Externally located brake and clutch handles
- Sturdy adjustable feet for safe working
- Freestanding model
- No heavy power necessary
- Safety foot pedal



SPECIFICATIONS*

Processing width	max. 1650 mm
Processing speed	max. 0-4 m/min
Roll diameter	max. 200 mm
Axis load	max. 60 kg
Main rollers diameter	140 mm
Roller Nip	max. 40 mm
Top roller heat assistance	low: 40° C, 1700 W high: 50° C, 1700 W
Hardness and shape of the rollers	65 Shore, top cylindrical, bottom crowned
Main rollers max pressure	1,6 N/mm pressure reg. 0-4 bar with internal compressor
Measurements H/W/D	1280 / 2175 / 700 mm
Weight	270 kg net.
Electrical requirements	1N/PE 230VAC/50Hz-60Hz; 1700W; 8A



*We reserve the right to make changes. Ask for current specifications.

05/23