



# ImagePerfect™ EG 95-501 PA

## White Gloss (FR)

ImagePerfect™ EG 95-501 PA White Gloss incorporates a PVC-free film, an advanced, water-based, permanent adhesive and PerfectApply technology. It is suitable for indoor and outdoor applications and has been specially created for digital printing on large-format inkjet printers, being compatible with latex and UV-cured inks.

ImagePerfect™ EG 95-501 PA White Gloss is suitable for a wide variety of indoor and medium-term outdoor applications on flat and slightly curved surfaces. It incorporates PerfectApply technology to increase repositionability and to facilitate bubble-free application. It promotes high levels of print quality, ensuring colourful images with vibrant area infills. The film is 100% PVC-free and it is equipped with an advanced, water-based adhesive that creates a strong final bond to ensure a secure, stable and durable finish. The 100% recycled liner is made from an FSC-certified base paper with a fossil-free LDPE coating that promotes excellent layflat. The core holders are made from 100% recycled, FSC-certified cardboard and 100% recycled LDPE; the cores are made from 100% recycled cardboard that are then 100% recyclable, the bags are made from 100% biodegradable polyethylene and the box is made from natural cardboard with no chemical bleaching that is sourced from FSC-certified plantations and its unique design ensures strength and integrity without needing (plastic) closure tapes. IP EverGreen 95-501 PA is produced at the Eikon factory in the UK, using only European-sourced raw materials in order to minimise the CO<sup>2</sup> footprint. For installation, we would recommend an application temperature of no less than 10°C. It must not be wet applied - i.e. dry application only. Laminate: ImagePerfect™ EG 95-502 Clear Gloss. Please make sure the printed EG 95-501 PA is completely dry before laminating. Adhesive transfer: As with other products within the PVC-free market space, IP EverGreen could manifest adhesive transfer (adhesive residue), upon removal of the film from the substrate. The levels of adhesive transfer could vary, depending on the installation substrate but, in all cases, the adhesive transfer is easily removable with IP Surface Cleaner. Recommendation: Spray IP Surface Cleaner onto the adhesive residue and leave for 15 seconds. Remove the adhesive residue with a squeegee. Spray IP Surface Cleaner onto the substrate. Wipe immediately with a clean cloth. ImagePerfect EverGreen digital products show a significant reduction in their environmental impact compared to the equivalent standard choices, evidenced by a 22% reduction in their carbon footprint. (certified: CarbonQuota 2023)

Specifications	
Description	PVC-free printable film
Colour	White gloss
Thickness	60mym
Weight	N/A
Adhesive	Advanced acrylic, permanent
Adhesive Strength	16N/25mm (Finat TM 1/24h)
Release Paper	100% recycled, FSC-certified base paper with a fossil-free LDPE coating, 140gsm siliconised
Temperature Range	-20°C to +70°C
Durability (unprinted)	5 years
Flame Retardancy	B-s1, d0
Shelf Life	2 years, 20°C / 50% humidity
End of Life / Disposal	Film: Recyclable   Liner: Recycled paper (not currently recyclable - could be used for refuse derived fuel (RDF))   Core: Recyclable   Core Holders: Recyclable   Bag: Biodegradable   Box: Recyclable

© October 2023 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners.



For more information about ImagePerfect please visit [www.imageperfect.com](http://www.imageperfect.com)

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom

Information on physical and chemical characteristics and values in this document are based upon tests we believe to be reliable and do not constitute a warranty. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of such products for their specific use, including, but not limited to, the application, conditions, maintenance, and the Purchaser shall assume all risk and liability of every nature in connection therewith. All technical data are subject to change without prior notice. In case of any ambiguities or differences between the English and foreign versions of this document, the English version shall be prevailing and leading.

Eikon gives no express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of fitness for any particular use and/or non-infringement. All products are sold subject to Eikon's general terms and conditions of sale. Eikon's aggregate liability, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoiced to Purchaser in respect of any occurrence or series of occurrences. In the event of improper use and/or incorrect processing that does not comply with our instructions, any and all liability is excluded. In no circumstances shall Eikon be liable for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.