PRODUCT DATA SHEET

Avery Dennison® MPI™ 2000

Issued: 10/2022

Introduction

Avery Dennison MPI 2000 is a gloss white polymeric self-adhesive vinyl, highly recommended for a wide range of applications on flat and slightly curved substrates.

Conversion

Avery Dennison MPI 2000 is a multi-purpose vinyl, developed for use on various super wide format printers using solvent-, eco/mild solvent-, UV curable and latex inks.

To enhance colour and protect images against UV radiation and abrasion, Avery Dennison MPI 2000 is recommended to be overlaminated with Avery Dennison DOL 2000 series.

Face Film

80 micron glossy white polymeric vinyl



Adhesive

permanent, acrylic based



Backing

two sides polyethylene coated kraft paper, 140 g/m2



Durability

7 years (unprinted, vertical exposure)



Shelf Life

2 years

Recommendations

- > Vehicle graphics (flat and slightly curved surfaces)
- » Interior & exterior signs
- » Window decoration

Features

- » Excellent printability and handling on selected printers
- » Excellent durability and outdoor performance
- » Excellent dimensional stability
- » HP Latex Certified

Physical Characteristics

Test method ¹	Results
ISO 534	80
ISO 534	120
FINAT FTM 14	0.3
Stored at 22° C/50-55 % RH	2
Unprinted, vertical exposure	7
EN13501-1	B-s1,d0
FINAT FTM-1, stainless steel	540
FINAT FTM-1, stainless steel	750
	≥ 10° C
	- 40 °C to + 80 °C
Mild acids	No effect
Mild alkalis	No effect
Applied to aluminium	No effect exposed to: oils, greases, aliphatic solvents, motor oils, heptane, kerosene and JP-4 fuel.
	ISO 534 ISO 534 FINAT FTM 14 Stored at 22° C/50-55 % RH Unprinted, vertical exposure EN13501-1 FINAT FTM-1, stainless steel FINAT FTM-1, stainless steel Mild acids Mild alkalis

Important

Information on physical and chemical characteristics and values in this document are based upon tests we believe to be reliable and do not constitute a warranty. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use.

All technical data are subject to change. In case of any ambiguities or differences between the English and foreign versions of this document, the English version shall be prevailing and leading.

- 1) Test methods: More information about our test methods can be found on our website.
- 2) Durability: The durability is based on middle European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the marking. For instance, in the case of signs facing south; in areas of long high temperature exposure such as southern European countries; in industrially polluted areas or high altitudes, exterior performance will be decreased.
- 3) Prolonged immersion in gasoline and similar fluids is not recommended.

Avery Dennison warrants that its Products meet its specifications. Avery Dennison gives no other express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of merchantability, fitness for any particular use and/or non infringement. All Avery Dennison products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purposes. The period of warranty is one (1) year from the date of shipment unless expressly provided otherwise in the product data sheet. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see http://lerms.europe.averydennison.com.

Avery Dennison's aggregate liability to Purchaser, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoices to Purchaser in respect of any occurrence or series of occurrences. In no circumstances shall Avery Dennison be liable to Purchaser for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.

© 2022 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.

