




HP Grip Gloss CP

Polymeric high-tack adhesive vinyl for hard-to-stick surfaces



The HP large format printing system—the complete solution

HP large format printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide uncompromising image quality, reliability, and consistency—with every print.



Achieve excellent print quality and adhesion

Efficient and reliable adhesive on “hard-to-stick” surfaces

HP Grip Gloss CP—with an aggressive, high-tack clear adhesive, is the ideal choice when mounting to demanding low surface energy plastics and powder-coated metal substrates. Save time during installation with a double-sided, lay-flat liner for easy installation.

Gain efficiency while providing outstanding colour fidelity

Help save time and gain efficiency with ICC profiles that help you quickly get the colour you need for a wide range of indoor and outdoor applications.

Help save time with a reliable, total HP solution

Original HP printing materials, Original HP inks, and HP large format printers are designed to work together as a system to provide reliable, consistent, quality results that help save time.

Target customers	Applications	Benefits
Print service providers	Demanding low-energy surfaces	Polymeric vinyl
	Heavy plant equipment	High-tack clear permanent adhesive that adheres to hard-to-stick surfaces like low surface energy plastics
	Indoor and outdoor advertising	Lay-flat liner for smooth production and installation
	Outdoor signage	Excellent print quality
	Permanent wall graphics	Compatible with Original HP Latex Inks; also solvent, eco-solvent, and UV-curable inks
	Ice hockey stadiums	



Technical specifications

HP Grip Gloss CP
For the latest ICC profiles/paper presets, please visit www.printos.com.

Ink compatibility	Compatible with Original HP Latex Inks; also solvent, eco-solvent, and UV-curable inks			
Thickness (base vinyl)	75 microns/2.9 mil per ISO 20534 Test Method			
Base vinyl	Polymeric			
Liner	130 g/m², double-sided PE-coated silicone paper			
Adhesive	Clear, permanent, high-tack solvent-based adhesive			
Opacity	> 85% per TAPPI T-425 Test Method			
Finish	Gloss, >70 gloss units at 60° reflection			
Water resistance	Water resistant with HP 871 and 831 Latex Inks¹			
Application temperature	5 to 35°C (41 to 95°F) on clean, dry surfaces			
Service temperature	-28 to 65°C (-18 to 149°F)			
Storage temperature	21 to 24°C (69 to 75°F)			
Storage humidity	50% RH			
Lamination	Cold lamination; recommend using HP Optimal Gloss or Matte Laminate			
Shelf life	2 years, unopened in original packaging			
Unprinted durability	Up to 7 years²			
Environmental	EU and UK REACH compliant³			
Country of origin	Product of the United Kingdom			
Ordering information	Product numbers	Roll sizes	UPC codes	Region
	9E0E2A	1372 mm x 45 m (54 in x 148 ft)	848412027723	Europe
	9E0E3A	1600 mm x 45 m (63 in x 148 ft)	848412027730	Europe
Warranty	HP large format printing materials are free from defects in materials and workmanship.			

¹ Performance varies based on printer and print profile. Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see HPLFMedia.com/hp/printpermanence.

² Outdoor unprinted display permanence rating based on white background colour change according to SAE J2020.

³ See the HP REACH Declaration published at [HP Printing Products and Consumable Supplies](#).