




HP Prime Gloss Air GP

Polymeric adhesive vinyl with grey permanent adhesive



The HP large format printing system—the complete solution

HP large format printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide uncompromising image quality, reliability, and consistency—with every print.



Produce outstanding, easy-to-install prints

See outstanding image quality and great hiding power

This high-gloss, polymeric adhesive vinyl offers outstanding image quality and “pop.” The grey permanent adhesive is opaque for maximum coverage. This vinyl installs easily with a lay-flat air release liner for fast installation.

Help gain efficiency while providing outstanding colour fidelity

Help save time and gain efficiency with ICC profiles that help you quickly get the colour you need, ideal for a wide range of indoor and outdoor applications.

Help save time with a reliable, total HP solution

Original HP printing materials, Original HP inks, and HP large format printers are designed to work together as a system to provide reliable, consistent, quality results that help save time.

Target customers	Applications	Benefits
Print service providers	Indoor and outdoor signage	Outstanding image quality on this intermediate polymeric vinyl
	Point-of-sale, retail displays	Grey, permanent adhesive provides opacity to achieve consistent image quality on multiple surfaces
	Exhibition and event graphics	Air release liner enables fast and easy installation
	Window graphics	Compatible with Original HP Latex Inks; also solvent, eco-solvent, and UV-curable inks

Technical specifications



HP Prime Gloss Air GP
For the latest ICC profiles/paper presets, please visit www.printos.com

Ink compatibility	Compatible with Original HP Latex Inks; also solvent, eco-solvent, and UV-curable inks			
Thickness (base vinyl)	75 microns/2.9 mil per ISO 20534 Test Method			
Base vinyl	Polymeric			
Liner	145 g/m², double-sided PE-coated air release liner			
Adhesive	Grey, permanent, water-based adhesive			
Opacity	>98% per TAPPI T-425 Test Method			
Finish	Gloss, >70 gloss units at 60° reflection			
Water resistance	Water resistant with HP 871 and 831 Latex Inks¹			
Lamination	Cold lamination; recommend using HP Prime Gloss or Matte Laminate			
Application temperature	5 to 35°C (41 to 95°F) on clean, dry surfaces			
Service temperature	-28 to 65°C (-18 to 149°F)			
Storage temperature	21 to 24°C (69 to 75°F)			
Storage humidity	50% RH			
Shelf life	2 years, unopened in original packaging			
Unprinted durability	Up to 5 years²			
Environmental	EU and UK REACH compliant³			
Country of origin	Product of the United Kingdom			
Ordering information	Product numbers	Roll sizes	UPC codes	Region
	9E0F2A	1372 mm x 45,7 m (54 in x 150 ft)	848412027808	Europe
	9E0F3A	1600 mm x 45,7 m (63 in x 150 ft)	848412027815	Europe
Warranty	HP large format printing materials are free from defects in materials and workmanship.			

¹ Performance varies based on printer and print profile. Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see HPLMedia.com/hp/printpermanence.
² Outdoor unprinted display permanence rating based on white background colour change according to SAE J2020.
³ See the HP REACH Declaration published at HP.Printing.Products.and.Consumable.Supplies.

