



# HP Prime Matte Laminate



## Polymeric clear, matte overlamine

**Provide image protection with this premium polymeric overlamine**

Make sure you're covered. With HP Prime Matte Laminate, your prints can withstand everyday wear and tear. It is recommended to partner with HP Prime Gloss Air GP.

**Cost-effective laminate**

Cost-effective, matte polymeric overlamine.

Target customers	Applications	Benefits
Print service providers	Overlamine	Cost-effective, polymeric overlamine



Technical specifications

HP Prime Matte Laminate

Thickness (base vinyl)	75 microns/2.9 mil per ISO 20534 Test Method			
Base vinyl	Polymeric			
Liner	90 g/m² clay coated liner			
Adhesive	Clear, permanent, water-based adhesive			
Finish	Matte			
Service temperature	-28 to 65°C (-18 to 149°F)			
Storage temperature	21 to 24°C (69 to 75°F)			
Storage humidity	50% RH			
Shelf life	2 years, unopened in original packaging			
Unprinted durability	Up to 5 years¹			
Environmental	EU and UK REACH compliant²			
Country of origin	Product of the United Kingdom			
Ordering information	Product numbers	Roll sizes	UPC codes	Region
	9E0F8A	1372 mm x 45,7 m (54 in x 150 ft)	848412027846	Europe
	9E0F9A	1600 mm x 45,7 m (63 in x 150 ft)	848412027853	Europe
Warranty	HP large format printing materials are free from defects in materials and workmanship.			

¹ Outdoor unprinted display permanence rating based on white background colour change according to SAE J2020.

² See the HP REACH Declaration published at [HP Printing Products and Consumable Supplies](#).

