



HP Optimal Gloss Laminate



Premium, polymeric clear, gloss overlaminate

Provide image protection with this premium polymeric overlaminate

Make sure you're covered. With HP Optimal Gloss Laminate, your prints can withstand everyday wear and tear. Recommended to partner with HP Optimal Gloss Air GRP or HP Grip Gloss CP.

Cost-effective laminate

Cost-effective, gloss polymeric overlaminate.

Target customers	Applications	Benefits
Print service providers	Overlaminate	Cost-effective, polymeric overlaminate



Technical specifications

HP Optimal Gloss Laminate

Thickness (base vinyl)	75 microns/2.9 mil per ISO 20534 Test Method			
Base vinyl	Polymeric			
Liner	90 g/m² clay coated liner			
Adhesive	Clear, permanent solvent-based adhesive			
Finish	Gloss, >70 gloss units at 60° reflection			
Service temperature	-28 to 65°C (-18 to 149°F)			
Storage temperature	21 to 24°C (69 to 75°F)			
Storage humidity	50% RH			
Lamination	Cold lamination			
Shelf life	2 years, unopened in original packaging			
Unprinted durability	Up to 7 years¹			
Environmental	EU and UK REACH compliant²			
Country of origin	Product of the United Kingdom			
Ordering information	Product numbers	Roll sizes	UPC codes	Region
	9E0E9A	1372 mm x 45,7 m (54 in x 150 ft)	848412027761	Europe
	9E0F0A	1600 mm x 45,7 m (63 in x 150 ft)	848412027778	Europe
Warranty	HP large format printing materials are free from defects in materials and workmanship.			

¹ Outdoor unprinted display permanence rating based on white background colour change according to SAE J2020.

² See the HP REACH Declaration published at [HP Printing Products and Consumable Supplies](#).

