



HP Optimal Matte Laminate



Premium, polymeric clear, matte overlamine

Provide image protection with this premium polymeric overlamine

Make sure you're covered. With HP Optimal Matte Laminate, your prints can withstand everyday wear and tear. Recommended to partner with HP Optimal Gloss Air GRP or HP Grip Gloss CP.

Cost-effective laminate

Cost-effective, matte polymeric overlamine.

Target customers	Applications	Benefits
Print service providers	Overlamine	Cost-effective, polymeric overlamine



Technical specifications

HP Optimal Matte Laminates

Thickness (base vinyl)	75 microns/2.9 mil per ISO 20534 Test Method			
Base vinyl	Polymeric			
Liner	90 g/m ² clay coated liner			
Adhesive	Clear, permanent solvent-based adhesive			
Finish	Matte			
Service temperature	-28 to 65°C (-18° to 149°F)			
Storage temperature	21 to 24°C (69 to 75°F)			
Storage humidity	50% RH			
Shelf life	2 years, unopened in original packaging			
Unprinted durability	Up to 7 years ¹			
Environmental	EU and UK REACH compliant ²			
Country of origin	Product of the United Kingdom			
Ordering information	Product numbers	Roll sizes	UPC codes	Region
	9E0E4A	1372 mm x 45,7 m (54 in x 150 ft)	848412027785	Europe
	9E0E5A	1600 mm x 45,7 m (63 in x 150 ft)	848412027792	Europe
Warranty	HP large format printing materials are free from defects in materials and workmanship.			

¹ Outdoor unprinted display permanence rating based on white background color change according to SAE J2020.

² See the HP REACH Declaration published at [HP Printing Products and Consumable Supplies](#).

