



HP Auto Gloss Laminate



Gloss laminate for fleet and vehicle graphics

Provide image protection with this conformable, soft, overlamine

Make sure you're covered. With HP Auto Gloss Laminate, your prints can withstand everyday wear and tear. It is recommended to partner with HP Auto Gloss Glide GP.

Cost-effective laminate

Cost-effective, conformable gloss polymeric overlamine.

Target customers	Applications	Benefits
Print service providers	Overlamine	Cost-effective, conformable laminate



Technical specifications

HP Auto Gloss Laminate

Thickness (base vinyl)	50 microns/2 mil per ISO 20534 Test Method			
Liner	90 g/m² clay coated liner			
Adhesive	Clear, permanent, solvent-based adhesive			
Finish	Gloss, >70 gloss units at 60° reflection			
Service temperature	-28 to 65°C (-18 to 149°F)			
Storage temperature	5 to 25°C (41 to 77°F)			
Storage humidity	50% RH			
Shelf life	2 years, unopened in original packaging			
Unprinted durability	Up to 9 years¹			
Environmental	EU and UK REACH compliant²			
Country of origin	Product of the United Kingdom			
Ordering information	Product numbers	Roll sizes	UPC codes	Region
	9E0D0A	1372 mm x 45,7 m (54 in x 150 ft)	848412027686	Europe
	9E0D1A	1600 mm x 45,7 m (63 in x 150 ft)	848412027693	Europe
Warranty	HP large format printing materials are free from defects in materials and workmanship.			

¹ Outdoor unprinted display permanence rating based on white background color change according to SAE J2020.

² See the HP REACH Declaration published at [HP Printing Products and Consumable Supplies](#).

