Expolinc Frame













BASIC PACKAGE

500 X 2 500 mm	9.5 kg
950 X 2 500 mm	10.4 kg
1 950 X 2 500 mm	13.4 kg
2 950 X 2 500 mm	16.5 kg '
3 950 X 2 500 mm	20.4 kg ³
4 950 X 2 500 mm	25.0 kg *

The package includes profiles packed in a delivery box.
*Incl. 1 supporting rod. **Incl. 2 supporting rods. ***Incl. 3 supporting rods.

STANDARD CASE XL PACKAGE

1950 X 2 500	mm	23.9	kg	
2 950 X 2 500	mm	27.0	kg	
3 950 X 2 500	mm	30.9	kg	**
4 950 X 2 500	mm	35.5	kg	***

The package includes profiles packed in Standard Case XL.
*Incl. 1 supporting rod. **Incl. 2 supporting rods. ***Incl. 3 supporting rods.



Addition, Standard Case XL: White and silver top shelf. Let us introduce Expolinc Frame. It requires no tools or specialized labor to setup. The unique magnetic connectors guide you to a smooth, stable and safe installation. The systems design consists of smooth, rounded edges along with profiles with high surface finish for a stylish environment.

The Expolinc Frame system - Whether you need a simple backwall or an advanced environment.

20 EXPOLING FRAME | EXPOLING.COM

Expolinc Frame

The choice is yours. Build whatever.

















Four different, double sided pair, single sided pair, single sided connection foot & double sided connection foot



idth (mm)	950
eight (mm)	2 495
epth (mm)	1000
eight	47.0 kg



Width (mm)	2 030
Height (mm)	
Depth (mm)	410
Weight	44 0 km





22 EXPOLINC FRAME | EXPOLINC.COM 23